

WHAT IS CLAIMED IS

1. A gas insulated switchgear comprising bus lines, disconnectors and a breaker:

5 a first metallic case containing said breaker, said first metallic case being earthed; and

a second metallic case containing said plurality of bus line disconnectors, or a plurality of second metallic cases containing said plurality of bus line disconnectors in a
10 single gas compartment, wherein

said first metallic case and said second metallic case are connected to each other through a gas partition spacer.

2. A gas insulated switchgear according to claim 1, which
15 is connected to a bus line through bushings, wherein

said plurality of bushings for leading a bus line are attached to said second metallic case with a preset spreading angle between the adjacent bushings for leading a bus line.

20 3. A gas insulated switchgear according to claim 2, wherein said spreading angle is a value within a range of 30 to 70 degrees.

4. A gas insulated switchgear according to any one of
25 claim 1, claim 2 and claim 3, wherein said bushing for leading a load is attached to said first metallic case so as to be slanted with respect to a direction intersecting at right

angle with a center axis of said first metallic case.

5. A gas insulated switchgear according to claim 4, wherein said bushing for leading a load and said plurality
5 of bushings for leading a bus line are attached to said first metallic case and said second metallic case on a plane slanting with respect to a vertical plane passing through center axes of said first metallic case or said second metallic case.

10

6. A gas insulated switchgear according to any one of claim 1 to claim 3, wherein an operating axis of said disconnecter intersect with a moving axis of a movable contact electrode of said disconnecter at nearly right angle.

15

7. A gas insulated switchgear according to any one of claim 1 to claim 3, wherein said metallic case has an earthing switch, said earthing switch is closed at an open-circuit position of the disconnecter, and opened at a closed-circuit
20 position of the disconnecter.

25

8. A gas insulated switchgear according to any one of claim 1 to claim 3, wherein said bushing is a duplex insulator tube made of FRP and silicone rubber.

9. A gas insulated switchgear according to claim 1, which comprises a bypass disconnecter for bypassing between a

leading point of said bushing for leading a load and said bus line; and a current detector for measuring a center conductor current of said bushing.

- 5 10. A gas insulation switchgear according to any one of claim 1 and claim 2, which comprises current transformers arranged in both sides of said breaker, and detecting accuracies of said current transformers in the both sides are different from each other.

10

11. A gas insulation switchgear according to claim 10, wherein a winding current type transformer is arranged as the transformer in one side of said breaker, and a Rogosky's coil type current transformer is arranged in the other side.

15

12. A gas insulation switchgear according to any one of claim 1 and claim 2, wherein a 3-position disconnecter is employed as said disconnecter.

- 20 13. A gas insulation switchgear according to claim 12, which comprises bushings for a double bus line, disconnectors being arranged between said two bushings and said breaker, a 3-position disconnecter being used as the disconnecter nearer to said breaker.

25